



1 SECOND FLOOR FINISH PLAN - UNIT A  
AT 35' / 1/8" = 1'-0"

FINISH LEGEND	
	VINYL COMPOSITION TILE
	FIELD-FINISHED WOOD FLOORING
	WOOD ATHLETIC FLOORING
	CARPET TILE
	NON-SLIP QUARRY TILE
	SEALED CONCRETE
	UNGLAZED CERAMIC TILE
	BROADLOOM CARPET
	TERRAZZO
	EPOXY FLOORING
	EXPOSED AGGREGATE
	EXTERIOR RUBBER PLAYGROUND FLOORING
	METAL FLOORING
	RUBBER TILE FLOORING
	WALLS:
	PAIN
	EPOXY PAINT
	GROUND FACE CMU
	GLAZED CERAMIC TILE
	UNPAINTED CMU BLOCK
	NON-SLIP STAINLESS STEEL WALL PANELS
	GLAZED CMU
	GLAZED CERAMIC TILE COVE BASE
	QUARRY TILE BASE
	SOLID SURFACE
	ACOUSTICAL WALL PANEL
	WALL SOUND DIFFUSER
	ABUSE-RESISTANT ACOUSTICAL WALL TREATMENT
	CARVED WOOD PANELING
	MOSAIC TILE
	CAST STONE CAPITAL
	CAST STONE CAPITAL

  

ELEVATION ABBREVIATIONS:	
CTR:	GLAZED CERAMIC TILE COVE BASE
QTR:	QUARRY TILE BASE
SS:	SOLID SURFACE
AWP:	ACOUSTICAL WALL PANEL
WSD:	WALL SOUND DIFFUSER
AR-WT:	ABUSE-RESISTANT ACOUSTICAL WALL TREATMENT
WP:	CARVED WOOD PANELING
MT:	MOSAIC TILE
CSC:	CAST STONE CAPITAL

  

GENERAL NOTES	
1. 7' X QUARRY TILE BASE TO BE IN SEaled CONCRETE AND QUARRY TILE.	12. FINISHES SHOWN IN ONE AREA OF ENTIRE ROOM OR CORRIDOR, UNLESS OTHERWISE NOTED.
2. ALL QUARRY TILE AND CERAMIC TILE TO HAVE 100% EPOXY GROUT.	13. SEE INTERIOR ELEVATIONS AT AREAS THAT REQUIRE MULTIPLE WALL FINISHES AT VARIOUS HEIGHTS.
3. TERRAZZO TO HAVE 1/8" GAUGE EXTRUDED ALUMINUM STRIP.	14. SEALED CONCRETE AT VARIOUS HEIGHTS FOR PRE-FABRICATED UNIT FLOORING.
4. ALL TERRAZZO FLOORS TO HAVE GLAZED CMU BASE.	15. ALL INTERIOR WALLS SHALL HAVE NON-REMOVABLE STAINLESS STEEL WALL PANELS. ELEVATOR CEILINGS SHALL HAVE FLUSH METAL PANELS WITH DOWN LIGHTS.
5. ALL ROOMS WITH EPOXY FLOORING EXCEPT CORRIDORS ARE TO HAVE SILVER FINISH AND OF HEIGHT REQUIRED TO PROTECT EDGES OF FLOOR PATTERN COMPLEXITY.	16. ALL STAIR LANDINGS TO HAVE AN ADA COMPLIANT TRANSITION.
6. SEE LOOP PATTERN PLANS FOR FLOOR PATTERN COMPLEXITY.	